

HOME SECURITY

○



(<https://technomax.it/wp-content/uploads/2018/12/gold-key-technomax.jpg>)

Gold Key WALL SAFETS

SERIE GOLD MURO

Casseforti a muro
Certificate EN 14450

(<https://technomax.it/en/serie/gold-wall-series/>)

Double Map Key
Front and Door thickness 10 mm.

- **Latest generation high security lock, with 8 asymmetrical and independent levers, UNI EN 1300 certified.**
It is based on the use of new oscillating anti-picking levers and special profile chin nets that oppose exceptional resistance to attacks carried out using the latest sophisticated handling systems with the use of special picks.
- **Double map key with special profile that can be duplicated with property card to prevent unauthorized duplication of keys.**
- Key extraction impossible when deadbolts are retracted.
- Nickel-plated steel deadbolts, revolving, 22 mm in diameter.
- Protection to the lock mechanism with manganese steel plate.
- Special door rabbets for exceptional resistance to break-in attempts using a sledgehammer.
- Robust internal welds made by robotic system.
- Perimeter welding of the face plate to the body carried out continuously by robotic system.
- Internal shelf (excluding mod. GK/1).
- Anchor tabs cut out on the 4 sides of the bottom with anti-tear function.
- Thermosetting powder coating with oven drying.

SPECIFICATIONS

Art	Alt. Est. (mm)	Larg. Est. (mm)	Ext. prof. (mm)	Alt. Int. (mm)	Larg. Int. (mm)	Prof. Int (mm)	Alt. Door (mm)	Larg. Door (mm)	Num. Caten. Orizz.	Num. Caten. Vert.	Weight (kg)	Volume (l)
GK/1	210	270	150	185	245	100	130	180	2	–	9.5	5.0
GK/2	210	270	200	185	245	150	130	180	2	–	10.5	7.0
GK/3B	210	340	150	185	315	100	140	250	2	–	12.5	6.5
GK/3	210	340	200	185	315	150	140	250	2	–	13	9
GK/4	270	390	200	245	365	150	195	300	2	1+1	18.0	14.0
GK/4L	270	390	240	245	365	190	195	300	2	1+1	19.0	18.0
GK/5	340	460	200	315	435	150	265	370	3	1+1	25.0	21.0
GK/5L	340	460	240	315	435	190	265	370	3	1+1	26.0	27.0
GK/5V	420	340	200	395	315	150	338	248	3	1+1	21.0	19.0
GK/6	420	480	230	395	455	180	345	390	3	2+2	33.5	33.0
GK/6L	420	480	280	395	455	230	345	390	3	2+2	34.5	43.0
GK/7	480	420	280	455	395	230	405	330	3	2+2	34.5	43.0
GK/7L	480	420	360	455	395	310	405	330	3	2+2	37.0	57.0

HERE YOU FIND SOMETHING