

# HOME SECURITY



(<https://technomax.it/wp-content/uploads/2018/12/gold-trony-technomax.jpg>)

## Gold Trony WALL SAFETS

### **SERIE GOLD MURO**

Casseforti a muro  
Certificate EN 14450

(<https://technomax.it/en/serie/gold-wall-series/>)

Electronic Digital Combination  
Front and Door thickness 10 mm.

- UNI EN 1300 certified lock controlled by a highly reliable electronic device with nonvolatile memory.
- Open/close with control knob and lock with electromagnet.
- Internal power supply with alkaline batteries (not included).
- Membrane keypad with 4 dedicated LEDs.
- External battery contacts made directly on the keyboard.
- Audible and visual alerts for typing confirmation, errors, and low internal batteries.
- Nickel-plated steel deadbolts, revolving, of 22 mm Ø (GT/1 – GT/2 – GT/3B – GT/3 Ø 18 mm fixed).
- Protection to the lock mechanism with manganese steel plate.
- Special door beats to resist mace break-in attempts longer.
- Robust internal welds made by robotic system.
- Perimeter welding of the face plate to the body carried out continuously by robotic system.
- Internal shelf (excluding mod. GT/1).
- Anchor tabs cut out on the 4 sides of the bottom with anti-tear function.
- Thermosetting powder coating with oven drying.

## SPECIFICATIONS

Art	Alt. Est. (mm)	Larg. Est. (mm)	Ext. prof. (mm)	Alt. Int. (mm)	Larg. Int. (mm)	Prof. Int (mm)	Alt. Door (mm)	Larg. Door (mm)	Num. Caten. Orizz.	Num. Caten. Vert.	Weight (kg)	Volume (l)
GT/1	210	270	150	185	245	100	130	180	2	–	9.5	4.5
GT/2	210	270	200	185	245	150	130	180	2	–	10.5	7.0
GT/3B	210	340	150	185	315	100	140	250	2	–	12.5	6.5
GT/3	210	340	200	185	315	150	140	250	2	–	13.0	9.0
GT/4	270	390	200	245	365	150	195	300	2	1+1	18.0	14.0
GT/4L	270	390	240	245	365	190	195	300	2	1+1	19.0	18.0
GT/5	340	460	200	315	435	150	265	370	3	1+1	25.0	21.0
GT/5L	340	460	240	315	435	190	265	370	3	1+1	26.0	27.0
GT/5V	420	340	200	395	315	150	338	248	3	1+1	21.0	19.0
GT/6	420	480	230	395	455	180	345	390	3	2+2	33.5	33.0
GT/6L	420	480	280	395	455	230	345	390	3	2+2	34.5	43.0
GT/7	480	420	280	455	395	230	405	330	3	2+2	34.5	43.0
GT/7L	480	420	360	455	395	310	405	330	3	2+2	37.0	57.0

**Upon request, all models can be equipped with a lock for mechanical emergency opening with a high-security double-bitted key (For models 4-5-6-7 lock EVO-LOCK.)**

Models with an emergency key GT/1P, GT/2P, GT/3BP, GT/3P are not UNI EN 14450:18 certified.

Product code of this series: add the letter "P" to the end of the standard product code.

Example: GT/3 without emergency key becomes GT/3P with emergency key, GT/4 becomes GT/4P, etc.

# HERE YOU FIND SOMETHING