Innovative safe for certified Grade II and III burglary protection



ProGuard

BURGLARY-RESISTANT PROTECTION

Key Features

- Burglary protection in accordance with the European standard, EN 1143-1, as certified by ECB•S for Grades II and III
- ProGuard's special barrier material provides certified burglary protection whilst also keeping the total weight of the safe down. Less weight means lower transportation costs and greater installation options.
- Innovations made with the Grade III models means that a higher level of protection can be offered in a safe with reduced wall thickness and increased interior capacity.
- The three-way boltwork is constructed with solid steel bolts.

- For additional security, ProGuard is fitted with an active relocker and anti-drilling plates have been incorporated into the boltwork to withstand burglary attempts.
- A Class A mechanical key lock or a Class B highsecurity electronic lock, approved in accordance with EN 1300, are both available as primary lock options. Electronic locks increase the level of security and prevent unauthorised access to the safe.
- Every model can be customised with a range of internal fittings to maximise storage capacity.
- ProGuard has a modern design with an ergonomic soft-touch handle.











Product Specifications

	External (mm)						Internal (mm)									
Model	Height		Width		Depth		Height		Width		Depth		Weight (kg)		Volume (litres)	
	Gr II	Gr III	Gr II	Gr III	Gr II	Gr III	Gr II	Gr III	Gr II	Gr III	Gr II	Gr III	Gr II	Gr III	Gr II	Gr III
60	530	-	500	-	521	-	430	-	400	-	360	-	250	-	62	-
110	690	690	600	600	561	561	590	600	500	510	386	396	334	315	114	121
150	875	875	600	600	561	561	775	785	500	510	386	396	402	377	150	159
200	1150	1150	600	600	561	561	1050	1060	500	510	386	396	501	486	203	214
300	1600	1600	600	600	561	561	1500	1510	500	510	386	396	655	655	290	305
350	1600	1600	675	675	585	585	1500	1510	575	585	410	420	731	703	354	371
450	1850	1850	675	675	616	615	1750	1760	575	585	440	450	981	813	443	463

Lock Options



Electronic Lock

As the primary locking option, ProGuard safes can be fitted with either a high-security electronic lock (Class B) or a key lock (Class A).

Dual locking is available from model 110. The primary lock can be complemented by a combination lock or both a key lock and electronic lock can be fitted.

All locks are tested by ECB•S and are certified in accordance with the EN 1300 standard.

ProGuard's high-security electronic lock – certified Class B by ECB•S – includes the following features:

- 1 master code, 1 supervisor code and 7 user codes.
- Time delay of up to 99 minutes between lock being operated and door being opened. Also equipped with time-delay override.
- Protective function to raise silent alarm if lock is being opened under duress.

Burglary Testing

ProGuard has been approved by ECB•S in accordance with the European standard, EN 1143-1, for burglary protection in Grades II and III.

A range of attack tools were used to test ProGuard's level of resistance, from basic tools to sophisticated thermal and electrical equipment.



Improved Capacity

Innovations made with the Grade III models have allowed the thickness of the safe walls to be reduced. This means that a safe with a higher level of protection will also offer greater capacity for the storing of valuable items and sensitive documents.

Internal Fittings



For 60: 20x375x350 For 110–300: 20x475x376 For 350: 20x550x400 For 450: 20x550x430



For 110–300: 37x455x376 For 350: 37x530x400 For 450: 20x550x430




Lockable drawer For 110–300: 100x460x336 For 350: 100x535x360 For 450: 100x535x390



Lockable compartment For 110–300: 335x467x358 For 350: 335x562x382 For 450: 335x562x412



Extensible tray For 110–300: 37x460x361 For 350: 37x535x385 For 450: 37x535x415



Extensible file frame For 110–300: 37x460x376 For 350–450: 37x535x376

*Reinforced shelf also available

Authorised dealer



www.chubbsafes.com